

### LOCAL DEVELOPMENT PLAN PROVISIONS

- a) This Local Development Plan (LDP) applies to 246-251, 256-265, 410-412, 429-433 &
- b) Unless otherwise varied by this LDP, all development shall be in accordance with the City of Kwinana Town Planning Scheme No. 2, the Residential Design Codes, and the Mandogalup West Local Structure Plan.
- c) Development Approval is exempt for any Single House that is compliant with the provisions of this LDP, the R-Codes, TPS2, and all relevant Local Planning Policies.
- d) Minor variations to the requirements of this Local Development plan may be approved by the City of Kwinana.

## 2. Dwelling Façade Treatment

All dwellings are to provide a high-quality design interface to the streetscape through the use of at least three of the following architectural design features:

- i. Articulation in dwelling facade (i.e. varied wall setbacks);
- ii. A minimum of two building materials, colours and/or finishes (E.g. render, brick, cladding);
- iii. Major habitable room openings incorporating large windows to provide
- iv. Roof forms that incorporate gables;
- v. A balcony, portico, or verandah; or
- vi. built-in planter box.

### 3. Street Set back

- a) All dwellings on land zoned R30 are to be set back a minimum of 3.0m and maximum of 5.0m from the primary street and 1.0m minimum from the secondary street, no averaging permitted.
- b) Lot 263 zoned R60 may be set back a minimum of 2.0m from the Primary Street. If Lot 263 is further subdivided or developed as Grouped Dwellings, the Primary Street set back shall apply to Townsend Parkway only (ie. a 1.0m minimum set back for both primary and secondary frontages applies to Gosse Street in all development
- c) For determining the maximum setback, facade elements or indentations are permitted to be set back greater than 5.0m where these constitute a minor proportion of the dwelling's front facade.
- d) Primary and secondary setbacks do not apply to eaves.
- e) Where a portico, porch, veranda or similar is provided, they may be setback a minimum of 2.0m from the primary street.
- f) For corner lots, where the major dwelling entry (front door) is orientated toward the secondary street, secondary street setbacks apply. Primary street setbacks apply to the other street, as designated on this LDP.

## 4. Fencing

- a) Fencing is not permitted within the primary street setback area.
- b) For secondary street boundaries, fencing shall be visually permeable above 1.2m behind the primary street setback, for a minimum length of 3.0m behind the truncation, with a habitable room addressing the street.
- c) Uniform estate fencing provided on private lots shall not be modified without written approval from the City of Kwinana and shall be maintained as visually permeable by landowners where applicable

## 5. Lot Boundary Set back

- a) For all lots zoned R30, a nil side set back is permissible to one side boundary behind the primary street setback line to a maximum of 4.0m from the rear boundary, unless otherwise designated on the LDP or where this boundary is to a secondary street.
- b) For Lot 263 zoned R60, a nil side set back may be provided to both side boundaries behind the primary and secondary street setback lines, with the exception of a 4m gap on the southern lot boundary to align with the location of any Outdoor Living Area (OLA) in Lot 264
- c) For lots with a frontage of 11 metres or less, or where otherwise designated on this LDP, nil setbacks are permitted to both side boundaries.

d) Where a nil side setback is permissible but not proposed, side setbacks shall conform to the requirements of the R-codes.

### 6. Open Space and Outdoor Living Area

Open space may be reduced to 35% of the site area subject to the provision of a an outdoor living area (OLA) with a minimum dimension of 4m and located behind the front setback area, with the following sizes and requirements:

- a. 24 sqm for R30 lots, with a minimum of 16sqm of the OLA to be uncovered.
- b. 16sqm for R60 lots, with a minimum of 11sqm of the OLA to be uncovered.

- a) Garages are to be set back a minimum of 4.5m from the primary street and are not to be forward of the dwelling alignment.
- b) All garages to have doors to enclose them.
- c) Garages may be aligned with the dwelling provided they do not exceed the garage setback line.
- d) Garages are to be set back 1.5m from the secondary street.
- e) Garages are permitted to have a nil setback to one boundary. The garage nil side setback is not required to be on the same nil side setback boundary as the dwelling.
- f) Where lots have a frontage of 12 metres or less, garages may exceed 50% of the primary lot frontage to a maximum of 60% of the primary lot frontage. Where garages exceed 50% of the primary lot frontage, they shall comply with the following:
- i. A clear indication of the dwelling entrance;
- ii. The dwelling entrance shall be the dominant feature of the facade and shall include a projecting portico or veranda with a minimum depth of 1.5 metres;
- iii. Garages are to be set back at least 0.5 metres behind the dwelling alignment;
- iv. For any single storey dwelling on a lot with a frontage less than 10 metres in width and where vehicle access is gained solely from the primary street, only a single width garage (including tandem) is permitted;
- v. Double garages are permitted on lots less than 10m wide where dwellings are two storeys and where major openings to habitable rooms are provided on the primary
- vi. For all lots where a footpath adjoins the boundary, the garage must be setback a minimum 4.5m from that boundary;
- Designated garage locations apply to lots identified on this Local Development Plan, referencing the side of the lot to which the garage must be located but do not prescribe boundary walls; and
- Access to on-site car parking spaces may be provided from either the primary or secondary street orientation unless otherwise designated on the Local Development Plan.

# 8. Vehicle Access

Lots affected by a 'No Vehicular Access' provision shall restrict vehicle access on boundaries identified on the map

# 9. Outbuildings

Where sheds and outbuildings do not match the construction materials and colours of the dwelling they are to be screened from public view.

- a) A minimum of one street tree per lot, and two street trees for corner lots are required.
- b) Street trees are to be generally located as shown on this LDP, subject to detailed landscape design
- c) Street trees are not to be relocated or removed by landowners.

# 11. Bushfire Management

The land subject to this LDP is within a bushfire prone area, as designated by the Department of Fire and Emergency Services. Those lots identified on this LDP as being subject to a Bushfire Management Plan require a Bushfire Attack Level Assessment and certification prior to construction, in accordance with Australian Standard 3959.

This LDP shall be read in conjunction with the approved Bushfire Management Plan.

**Apsley** 

CADASTRAL INFORMATION SOURCE: C&W YYMMDD: 200106 DWG REF: 6027-CAD PRO IECTION: PCG94 CAD PRECAL SOURCE: MNG YYMMDD: 200311 DWG RFF: 96755pr-025



SIZE A3 1:2000

CITY ASSESSMENT COMMENTS 200623 DEVELOPER FENCING LOT 263 200608 FENCE HEIGHTS FOR LOT 263 200604 ED AB AB ADD LOT 263 200526 ED ADD LOT 453 200318 ΚV PROVISION UPDATE TO 1A 200317 SB AB VARIOUS LIPDATES 200226 DRAWN APPR'D LOCAL DEVELOPMENT PLAN (2)

**Apsley Stage 2** City of Kwinana

DRAW NO. REV. REF NO. QUB MAN RD1 206